

# Gas/Air Quality Monitor Model Airwell Plus II

Single or Dual Gases  
In/Outdoor Air  
Toxic Gases  
Home/Working Area

## Feature

Easy Operation  
Light weight Truly portable  
Auto Zero calibration



## Specification

Mesurable components : O2 CO CO2 SO2 NO2 NO  
HF HCL TVOC CH4 Formaldehyde (CH2O)  
NH3 O3 H2S Mercaptan H2

Measuring range : sub ppm to percent ( Consult factory)

Sampling : Sampling or Duiffusion Type

Resolution & accuracy : Depends on range of sensor and application

Detection type : Electrochemical - Life 16 months <  
NDIR (CO2 HC CH4) - Life 5 years  
PID (TVOC) - Life 18 month <

Weight : 1.2 kg

Size : 80D x 150W x 235H mm

Power -Li-Ion rechargeable Battery - Safe Long life

Rechargeable Adaptor- Speed Charge : 20 minute for 6~ 8 hours operation

Minutes Average Data measuring

1 ~ 60 Minutes Average Data Storage

Real-time data RS232 digital output

General Purpose Case material : Aluminium

Standard accessories - AC adaptor operation manual RS232 PC cable

Display : 4 line 20 Character Blue backlight

Alarm factory set

Optional - Sampling pump (Flow rate ~500CC/min)

Carrying case

Wireless Accessories

Please select Component and Range (Consult Factory)

## KINSCO Technology Co.,Ltd

46-20 suyü 5 dong Kang buk Gu Seoul korea 142-891

<http://www.kinsco.co.kr> email : [kinsco@empal.com](mailto:kinsco@empal.com) 822)908-9667 fax)822)902-9667