

# 실내외 설치형 악취 및 유해 가스 모니터

## 특징

- 방진 방습 옥내외 설치형
- 측정감도 측정 범위에 따라 3 ppb ~ 10 ppb
- 경량
- 측정값 연속측정 및 전송
- 평균값저장
- 자동 0점 조정
- 간편한 설치와 사용
- 실측값 무선송신 기능(선택)

고정 설치형 단일 성분 가스 측정기  
실내외 공기질 측정  
현장 가스 누출 탐지  
유해 및 악취성분 측정  
수처리장 악취성분 측정  
사무실 연구실의 가스 안전  
가정용 공기질과 가스 안전  
농업 에너지환경 관련산업 연구  
공기질관련 측정장치연구

Model Airwell Plus M



## Specification

Measurable Components : (1 성분 선택)

기타 성분 : O<sub>2</sub> O<sub>3</sub> CO CO<sub>2</sub> SO<sub>2</sub> NO NO<sub>2</sub> N<sub>2</sub>O

HCHO HF HCN HCL CL<sub>2</sub> CH<sub>4</sub> NH<sub>3</sub> H<sub>2</sub> H<sub>2</sub>S

Type of Sensor : Electrochemical - Life about 16 months

NDIR - Life over 5 years

PID - Lamp Life 16 months

Measuring range : sub ppm to % (Consult Factory)

Resolution & accuracy : Depends on Sensor and measuring range

Sampling : Diffusion & Built-in Sample pump

User selectable 1~60 minutes average data measuring and storage

100 data Storage

Rs 232 digital output

Display : 4 line 20 character Blue back light LCD

Factory set alarm

Membrane Keypad

General purpose : Water & dust proof

Standard accessories : AC adaptor, Operation manual, RS232 9pin cable

Operational power : 220 VAC (110 VAC option)

Size : 210 x195 x 185 (HxWxD)mm Material : ABS Color : white Ivory

Weight : 1.5 kg

Options -

1) Sampling pump ; sample flow rate : 300 cc/min ~

2) Wireless communication accessories

3) Aluminium Carrying case

4) Battery operation : Li-Ion Rechargeable battery (over 6~ hours )

Specification can be changed without notice for the improvement of performance



(株)韓國産業機器

KINSCO Technology Co.,Ltd

46-20 suyu 5dong Kang buk Gu Seoul Korea 142-891

82) 2-908-9667 fax) 82)-2-902-9667 kinsco@empal.com www.kinsco.co.kr